



CinemaStar® Z7K500

Highlights

- First 7200 RPM, 500GB¹ in a 7mm, single-disk design
- Advanced Format with 512-byte emulation
- Video hard drive with 24x7 availability⁵
- Low power utilization to help reduce energy costs
- SmoothStream™ technology
- Silent-seek acoustics for quiet operation
- SMART Command Transport (SCT) for streaming optimization

Applications/ Environments

- Digital Video Recorders (DVR)
- Set-top Boxes
- DVR-enabled Televisions
- High-end Audio Systems
- Video Surveillance Systems



320GB and 250GB
7200 RPM | SATA 6Gb/s



Expanding the CinemaStar Family

CinemaStar® Z7K500 is the industry's first one-disk, 7mm, 7200 RPM, 2.5-inch drive designed for high-performance A/V streaming with capacities from 250GB to 500GB. These 500GB per platter models use Advanced Format and have been customized to support digital video and surveillance applications. Advanced Format increases physical sector size from 512 bytes to 4096 (4K) bytes, thereby increasing capacities and error correction capabilities. Consult the HGST Advanced Format Technology Brief for more information on these drives. The slimmer CinemaStar Z7K500 is designed as a direct replacement for standard 9.5mm HDDs and is well suited for TV integration, multi-tuner digital video recorders and set top boxes.



Designed For Digital Video Solutions

An exceptional blend of audio/visual (AV) features fine tunes the CinemaStar Z7K500 for video storage applications. HGST SmoothStream technology supports the ATA-7 streaming command set, and SCT provides time-limited error recovery and thermal monitoring capabilities. CinemaStar Z7K500 is offered with silent-seek acoustics for excellent sound quality. HGST continues to provide near silent operation to make the Z7K500 an ideal choice for home DVR applications and surveillance systems. The CinemaStar Z7K500 is an eco-friendly choice due to its low power consumption and halogen-free production. This sixth generation 2.5-inch CinemaStar drive, with its superior performance, balanced capacity and power-management delivers greater design flexibility for next-generation video systems.



Reliability Leadership

CinemaStar Z7K500 elevates hard drive reliability to new levels with an improved protection scheme for power fluctuation and enhanced TFC for improved error rates. HGST offers customers system design and integration services including, but not limited to hard drive selection, optimization, software compatibility assessment, performance profiling, problem analysis and reliability consultation. Team HGST is ready to help you deliver a successful video device. The HGST CinemaStar product line is optimized for video applications on any size system.

Features and Benefits

	Feature / Function	Benefits
Capacity	Up to 500GB storage	Up to 185 hours of high-definition video, 500 hours of standard video, 178 movies, 125,000 4-min songs *
Reliability	<ul style="list-style-type: none"> • Thermal Fly-height Control (TFC) • Media maintenance 	<ul style="list-style-type: none"> • Improved reliability • Extends recording life and capabilities
Performance	First 7200 RPM, 32MB cache model <ul style="list-style-type: none"> • SMART Command Transport (SCT) • ERP Control 	Compact, high-performance video storage Smoother streaming and improved error recovery timing for optimum A/V performance
Interface	SATA 6Gb/s	Higher data throughput
Eco-friendly	<ul style="list-style-type: none"> • 1.7W operating power • Halogen-free design 	<ul style="list-style-type: none"> • Reduces energy cost in A/V applications • Smaller carbon footprint
Acoustics	Silent seek	Ultra-quiet operation for improved sound quality

* Actual storage may vary depending on the compression rate applied. Capacities may not be combined.



CinemaStar® Z7K500

Specifications

Model / Part No.	HCC725050A7E630 / OJ26075 HCC725032A7E630 / OJ26073 HCC725025A7E630 / OJ26072
Configuration	
Interface	SATA 6Gb/s
Capacity ¹ (GB)	500 / 320 / 250
Sector size ² (bytes)	512e
Recording zones	30
Areal density (max, Gbit/sq.in.)	630
Performance	
Data buffer ³ (MB)	32
Rotational speed (RPM)	7200
Latency average (ms)	4.2
Media transfer rate (max, Mbits/s)	1369
Interface transfer rate (MB/s)	600
Seek time, read ⁴ (ms, typical)	15
Reliability	
Load/Unload cycle	600,000
Power on hours (POH) per month	732
Availability ⁵ (hrs/day x days/wk)	24x7
Power	
Requirement	+5VDC (+-5%)
Startup (W, peak, max)	4.5
Operating ⁶ (W)	1.7
Low power idle ⁷ (W, average)	0.8
Physical size	
Height (max, mm)	7
Dimensions (width x depth, mm)	70 x 100
Weight (max, g)	95
Environmental (operating)	
Shock (half-sine wave,)	325G/2ms
Operating temperature (top cover)	0° to 70° C
Environmental (non-operating)	
Shock (half-sine wave)	350G/2 ms
Ambient temperature	-40° to 65° C
Acoustics (A-weighted sound power)	
Idle (Bels, typical)	2.3
Operating ⁶ (Bels, typical)	2.4

HGST Quality and Service

HGST's mobile hard drives are designed to the highest quality standards and contain field-proven components. HGST provides worldwide technical support and integration services to enable global customers to bring their products to market quickly.

How to read the Ultrastar model number

HCC725050A7E630 = 500GB, SATA 6Gb/s
 H = HGST
 C = CinemaStar
 C = Compact
 72 = 7200 RPM
 50 = Full capacity — 500GB
 50 = Capacity this model, 50 = 500GB
 (32 = 320GB, 25 = 250GB)
 A = Generation code
 7 = 7mm z-height
 E6 = SATA 6Gb/s with 512 emulation
 3 = 32MB cache
 0 = Reserved

¹ One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the hard drive, the computer's operating system, and other factors.

² Advanced Format drive: 4K physical sectors with 512 byte emulation

³ Portion of buffer capacity used for drive firmware

⁴ Excludes command overhead

⁵ Designed for low duty cycle, non mission-critical digital video applications. Note that customer environments vary from application to application.

⁶ Assumes CE operational conditions, IDEMA 3 streams

⁷ 5 minutes after last host command

© 2016 HGST, Inc. 3403 Yerba Buena Road, San Jose, CA 95135 USA. Produced in the United States 5/12 rev. 2/16. All rights reserved.

CinemaStar is a registered trademark and SmoothStream is a trademark of HGST, Inc. and its affiliates in the United States and/or other countries.

HGST trademarks are intended and authorized for use only in countries and jurisdictions in which HGST has obtained the rights to use, market and advertise the brand. Contact HGST for additional information. HGST shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to HGST's products, programs, or services do not imply that HGST intends to make these available in all countries in which it operates. Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hgst.com/support, for additional information on product specifications. Photographs may show design models.

Information & Technical Support

www.hgst.com

www.hgst.com/support

Partners First Program

channelpartners@hgst.com

www.hgst.com/partners