



DATA SHEET

Trusted. Efficient. Versatile.
Exos 7E2



The Seagate® Exos™ 7E2 enterprise hard drives with 1TB and 2TB capacities are specifically designed to address the needs of storing unstructured data cost-effectively. The traditional 512-native format with a 6Gb/s SATA interface ensures easy integration into legacy storage servers and systems.



Best-Fit Applications

- Legacy mainstream applications requiring 512n block size
- Hyperscale applications/cloud data centers with replicated storage
- Scale-out data centers and Big Data analytics
- High-capacity density RAID storage
- Mainstream enterprise external storage arrays (SAN, NAS, DAS)
- Distributed file systems, including Hadoop and Ceph
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance

Reliable Data Center-Grade Hard Drive Within Reach

The Exos 7E2 hard drives support up to 2TB per drive,¹ offering economical storage for traditional 512-native infrastructures requiring a highly reliable enterprise hard drive. Exos 7E2 provides the most cost-effective, reliable access to unstructured data in bulk storage applications. Built on field-proven 9th generation conventional magnetic recording (CMR) technology, the Exos 7E2 drive helps to catalyze the datasphere, enabling data center architects and IT professionals to deliver trusted performance, rock-solid reliability, ironclad security and low TCO for demanding 24×7 operations.

Robust Bulk Data Storage for a 24×7 World

The Exos 7E2 hard drives are proven, enterprise-class hard drives with enterprise-grade reliability backed by a 2 million hour MTBF rating. With state-of-the-art cache, on the fly error-correction algorithms and rotational vibration design, the Exos 7E2 helps ensure consistent performance in replicated and RAID multi-drive systems.

Consistent, High Performance and Compatibility for Legacy Data Center Applications

Meet your storage workload requirements with the most efficient and cost-effective SATA 6Gb/s drive in a 3.5-inch data center footprint. With user-definable innovative technology advancements like PowerChoice™ and Seagate RAID Rebuild®, you can tailor your bulk storage requirements for even greater improvements in your TCO.

Enhanced Enterprise Reliability, Data Protection and Security

The Exos 7E2 series delivers firmware security features to help protect data where it lives—on the drive. Exos 7E2 hard drives safeguard firmware with authentic Secure Downloads & Diagnostics.

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.



Specifications	512n SATA	
Capacity	2TB	1TB
Base Model	ST2000NM0008	ST1000NM0008
Features		
SuperParity	Yes	Yes
Low Halogen	Yes	Yes
PowerChoice™ Technology	Yes	Yes
Seagate RAID Rebuild® Technology	Yes	Yes
SD&D Firmware Security	Yes	Yes
Cache	128MB	128MB
Reliability/Data Integrity		
Vibration, Nonoperating: 10Hz to 500Hz (Grms)	5	5
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.44%	0.44%
Nonrecoverable Read Errors per Bits Read, Max	1 sector per 10E15	1 sector per 10E15
Power-On Hours per Year (24x7)	8760	8760
Bytes per Sector	512	512
Limited Warranty (years)	5	5
Performance		
Spindle Speed (RPM)	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s, MiB/s)	194	194
Average Latency (ms)	4.16	4.16
Interface Ports	Single	Single
Rotation Vibration @ 1500 Hz (rad/s ²)	12.5	12.5
Power Consumption		
Idle Power, Average (W)	4.7	4.7
Typical Operating (W)	7.0	7.0
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V
Environmental		
Temperature, Operating (°C)	5°C – 60°C	5°C – 60°C
Shock, Operating 2ms (Read/Write) (Gs)	70/40Gs	70/40Gs
Shock, Nonoperating, 1ms/2ms (Gs)	200/300	200/300
Physical		
Height (in/mm, max) ¹	26.1mm/1.028in	26.1mm/1.028in
Width (mm/in, max) ¹	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max) ¹	147.00mm/5.787in	147.00mm/5.787in
Weight (g/lb)	550g/1.212lb	550g/1.212lb
Carton Unit Quantity	20	20
Cartons per Pallet	40	40
Cartons per Layer	8	8

¹ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.

AMERICAS	Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA	Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, the Exos logo, PowerChoice and Seagate RAID Rebuild are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1956.1-1709US September 2017